


MODEL 8772 15 TON AXLE JACK

JACK INCLUDES:

- Hard Chrome Plated Cylinder and Plunger Bores
- Extension screw and hand pump parts are plated to resist corrosion
- Manual Hand Pump
- Skydrol Resistant Paint (safety yellow)
- Factory Proof Load @ 150% of rated capacity
- 1 Year Warranty
- Fully Enclosed Shipping Container

Model 8772 is built to withstand harsh environmental conditions, rugged use and to provide many years of continuous service. Our customers are guaranteed a quality product with each purchase and are assured of our continued product support whenever and wherever the need arises.



MODEL 8772 15 TON AXLE JACK

SPECIFICATIONS

Rated Capacity: 15 tons (13.6 m. tons)
 Side Load: 15% of vertical load
 Low Height: 5.25 inches (133 mm)
 Hydraulic Lift: 5 inches (127 mm)
 Extension Screw: 2.25 inches (57 mm)
 Total Extended Height: 12.5 inches (318 mm)
 Oil Pressure at Rated Capacity: 4315 psig (303 kg/sq cm)
 Safety Pop-off Valve set at: 16.5 tons (15.0 m. tons)
 Proof Load: 22.5 tons (20.4 m. tons)
 Reservoir Capacity: 0.4 gallons (1.5 liters)
 Hydraulic Fluid: MIL-H-5606 or equivalent
 Approximate Jack Net Weight: 40 lbs (18 kg)

MODEL 8772 TYPICAL AIRCRAFT APPLICATIONS

Nose Landing Gear	Main Landing Gear
RJ	RJ

OPTIONAL EQUIPMENT CODES: (Specify at time of order)

SPC: Special Paint Color (yellow is standard)

8772PK: Repair Kit

SHIPPING DATA

NOTE: Model 8772 jack is shipped in a fully enclosed shipping container.

Length inch (mm)	Width inch (mm)	Height inch (mm)	Weight lbs (kg)
26 (660)	9 (229)	18 (457)	60 (27)