


MODEL 8811
105 TON FIXED HEIGHT TRIPOD JACK




JACK INCLUDES:

- Manual Hand Pump with high, medium and low pressure operating positions
- Heavy Duty Tow Handle and Swivel Casters with Swivel Locks for improved towing
- Hydraulic "Thermal" Relief Valve for added protection and safety in the event of internal fluid expansion due to temperature
- Secondary Cylinder Seal for protection against contaminants and to prolong life of primary seal
- Rain Hat (covers jack upper head)
- Hard Chrome Plated Cylinder Bore
- All unpainted parts are plated to resist corrosion
- Skydrol Resistant Paint (safety yellow)
- Factory Proof Load @ 150% of rated capacity
- 3 Year Warranty
- Shipping Skid

STANDARD OPTIONS:

- Air Operated Hydraulic Pump
- Load Gauge for load indication (reads tons/psig)
- Adjustable Swivel Feet with Level for leveling jack
- Hydraulic Operated Casters provide ease in jack leveling and increased ground clearance for towing
- Platform Mounted Operating Controls allow one person to position locknut while controlling lifting and lowering operations
- Ladder/platform

Model 8811 is built to withstand harsh environmental conditions, rugged use and to provide many years of continuous service. Our customers are guaranteed a quality product with each purchase and are assured of our continued product support whenever and wherever the need arises.



MODEL 8811

105 TON FIXED HEIGHT TRIPOD JACK

SPECIFICATIONS

Rated Capacity: 105 tons (95.3 m. tons)
 Side Load: 15% of vertical load
 Roll Under Height: 99.5 inches (2527 mm)
 Low Height: 98 inches (2489 mm)
 Hydraulic Lift: 74 inches (1880 mm)
 Extension Screw: 24 inches (610 mm)
 Total Extended Height: 196 inches (4978 mm)
 Oil Pressure at Rated Capacity: 3280 psig (231 kg/sq cm)
 Safety Pop-off Valves
 System Relief Valve set at: 116 tons (105.2 m. tons)
 Thermal Relief Valve set at: 131 tons (118.8 m. tons)
 Proof Load: 158 tons (143.3 m. tons)
 Reservoir Capacity: 26 gallons (98.4 liters)
 Hydraulic Fluid: MIL-H-5606 or equivalent
 Maximum Towing Speed: 5 mph (8 km/h)
 Approximate Jack Net Weight: 4800 lbs (2177 kg)

MODEL 8811 TYPICAL AIRCRAFT APPLICATIONS

Wing or Body

A319, A320, A321, B747, B757*, B767, B777

*Specify 3/4" Female Spherical Radius Ship Adapter p/n 73318-1 for this application

OPTIONAL EQUIPMENT CODES: (Specify at time of order)

AP: Air Operated Hydraulic Pump
 GA: Load Gauge
 AF: Adjustable Swivel Foot
 HC: Adjustable Swivel Foot with Hydraulic Caster
 SA: Shock Absorber (requires hydraulic caster)
 LA: Ladder/platform
 RC: Platform Mounted Operating Controls
 SPC: Special Paint Color (yellow is standard)
 8811PK: Repair Kit
 73318-1: 3/4" Female Spherical Radius Ship Adapter

PACKAGING CODES & OPTIONS: (Specify at time of order)

KD: Domestic Skid - Jack Knocked Down
 ECKD: Export Crate - Jack Knocked Down (Additional Cost)

SHIPPING DATA

NOTE: Unless otherwise specified, Model 8811 jack is shipped on a wood skid in the knocked down condition. Refer to Malabar Tripod Jack Shipping Supplement for additional packaging information.

Packaging Code	Length inch (mm)	Width inch (mm)	Height inch (mm)	Weight lbs (kg)	Total Weight lbs (kg)
KD (leg skid)	113 (2870)	40 (1016)	38 (965)	2200 (998)	5400 (2449)
	(cylinder skid) 107 (2718)	40 (1016)	50 (1270)	3200 (1452)	
ECKD (leg crate)	115 (2921)	45 (1143)	41 (1041)	2500 (1134)	6000 (2722)
	(cylinder crate) 109 (2769)	45 (1143)	53 (1346)	3500 (1588)	

MALABAR International

Issue: 6/99

PLANT: 220 WEST LOS ANGELES AVENUE, SIMI VALLEY, CALIFORNIA 93065 • (805) 581-0116 • FAX (805) 584-1624
 MAIL: P.O. BOX 367, SIMI VALLEY, CALIFORNIA 93062 • E-mail: sales@malabar.com • Web site: http://www.malabar.com